

Canon**XF705**

RÉSOLUTION	ÉCHANTILLONNAGE DES COULEURS	PROFONDEUR DE BITS	FRÉQUENCE D'IMAGE	CODEC	Mbit/s
3840 × 2160	YCC 4:2:2	10 bits	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.265/HEVC	160 Mbit/s / 110 Mbit/s
1920 × 1080	YCC 4:2:2	10 bits	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.265/HEVC	60 Mbit/s / 45 Mbit/s
			59,94i, 50,00i		60 Mbit/s / 45 Mbit/s
			120P, 100P		180 Mbit/s
3840 × 2160	YCC 4:2:0	8 bits	29,97P, 23,98P, 25,00P	H.264/XF-AVC	160 Mbit/s
1920 × 1080	YCC 4:2:0	8 bits	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.264/XF-AVC	45 Mbit/s
			59,94i, 50,00i	H.264/XF-AVC	45 Mbit/s
			120P, 100P	H.264/XF-AVC	180 Mbit/s
1280 × 720	YCC 4:2:0	8 bits	59,94P	H.264/XF-AVC	8 Mbit/s
1920 × 1080	YCC 4:2:0	8 bits	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.264/MP4	35 Mbit/s / 8 Mbit/s